

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059


PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 16FF



Thickness (mm)	2.5		
Weight (kg/m²)	2.1		
Max Width (mm)	2000		
Min Pulley diameter	50		
Nosebar Diameter (mm)	N/A		
Minimum back flex	75		
Load for 1% elongation (N/mm)	3		
Max working Tension	5		
Op temp (min) deg	-10	Op temp (max) deg	80
Conveying side material	POLYESTER/COTTON		
Conveying side colour	WHITE		
Underside Material	POLYESTER/COTTON		
Underside feature	UNCOATED		
Underside colour	WHITE		
Co- efficient of friction (u)	0.12		
Applications	Dough belt for accumulators, diverters, plough, flat and skid bed conveyors.		
Characteristics	Anti-sticking, good resistance to oils and grease, excellent tracking characteristics, good lateral stability and low friction surface.		
Food approval	FDA/USDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.