



15 PELMET CRESCENT
 THOMASTOWN VIC 3074
 AUSTRALIA
 P.O. BOX 2106
 GREENVALE 3059

PHONE: (03) 9462 4544
 FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 2CCM



Thickness (mm)	3.2	
Weight (kg/m²)	4	
Max Width (mm)	2000	
Min Pulley diameter	70	
Nosebar Diameter (mm)	N/A	
Minimum back flex	100	
Load for 1% elongation (N/mm)	8	
Max working Tension	12	
Op temp (min) deg	-10	Op temp (max) deg 80
Conveying side material	PVC	
Conveying side colour	WHITE	
Underside Material	SMOOTH	
Underside feature	MATT	
Underside colour	WHITE	
Co- efficient of friction (u)	0.45	
Applications		
Characteristics		
Food approval	FDA/USDA	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.