



15 PELMET CRESCENT
 THOMASTOWN VIC 3074
 AUSTRALIA
 P.O. BOX 2106
 GREENVALE 3059

PHONE: (03) 9462 4544

FAX: (03) 9462 4744

A.C.N. 067 591 155


A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 2CFM (WHITE)



Thickness (mm)	2.5	
Weight (kg/m²)	2.8	
Max Width (mm)	2000	
Min Pulley diameter	50	
Nosebar Diameter (mm)	N/A	
Minimum back flex	75	
Load for 1% elongation (N/mm)	8	
Max working Tension	10	
Op temp (min) deg	-10	Op temp (max) deg 80
Conveying side material	PVC	
Conveying side colour	WHITE	
Underside Material	POLYESTER	
Underside feature	UNCOATED	
Underside colour	NATURAL	
Co- efficient of friction (u)	0.15	
Applications	Food Industry, Direct food contact	
Characteristics	Food grade.	
Food approval	FDA/USDA	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.