

F&D



15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059


PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 2LGM (WHITE)



Thickness (mm)	2.8		
Weight (kg/m²)	2.2		
Max Width (mm)	2000		
Min Pulley diameter	50		
Minimum back flex	75		
Load for 1% elongation (daN/cm)	10		
Max working Tension	10		
Op temp (min) deg	-10	Op temp (max) deg	80+
Conveying side material	PVC		
Conveying side colour	WHITE		
Underside Material	POLYESTER		
Underside feature	UNCOATED		
Underside colour	NATURAL		
Co- efficient of friction (u)	0.15		
Applications	For flat and skid bed conveyors, box, parcel and carton conveying, and for incline or decline conveyors.		
Characteristics	Good resistance to oil and grease, excellent tracking characteristics, suitable for fitting of flights, profiles and sidewalls.		
Food approval	FDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.