

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 2RT BLACK



Thickness (mm)	5		
Weight (kg/m²)	4		
Max Width (mm)	2000		
Min Pulley diameter	60		
Nosebar Diameter (mm)	N/A		
Minimum back flex	100		
Load for 1% elongation (N/mm)	8		
Max working Tension	16		
Op temp (min) deg	-10	Op temp (max) deg	70
Conveying side material	PVC		
Conveying side colour	BLACK		
Underside Material	PET		
Underside feature	UNCOATED		
Underside colour	NATURAL		
Co- efficient of friction (u)	0.15		
Applications	Inclined conveyor for luggages or packed goods.		
Characteristics	Very high grip top cover. Anti-static.		
Food approval	NO		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.