



15 PELMET CRESCENT
 THOMASTOWN VIC 3074
 AUSTRALIA
 P.O. BOX 2106
 GREENVALE 3059


PHONE: (03) 9462 4544
 FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 2RT WHITE



Thickness (mm)	5.5	
Weight (kg/m²)	4.7	
Max Width (mm)	1500	
Min Pulley diameter	60	
Nosebar Diameter (mm)	N/A	
Minimum back flex	90	
Load for 1% elongation (N/mm)	8	
Max working Tension	16	
Op temp (min) deg	-10	Op temp (max) deg 80
Conveying side material	PVC/ROUGH TOP	
Conveying side colour	WHITE	
Underside Material	POLYESTER	
Underside feature	UNCOATED	
Underside colour	NATURAL	
Co-efficient of friction (u)	0.15	
Applications	Incline and decline rough top, used in wide range of food industry.	
Characteristics	Very high grip top cover.	
Food approval	FDA	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.