



15 PELMET CRESCENT
 THOMASTOWN VIC 3074
 AUSTRALIA
 P.O. BOX 2106
 GREENVALE 3059


PHONE: (03) 9462 4544
 FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 2TCE



| | | |
|--------------------------------------|---|------------------------------|
| Thickness (mm) | 1.6 | |
| Weight (kg/m²) | 1.5 | |
| Max Width (mm) | 700 | |
| Min Pulley diameter | 40 | |
| Nosebar Diameter (mm) | N/A | |
| Minimum back flex | 60 | |
| Load for 1% elongation (N/mm) | 9 | |
| Max working Tension | 15 | |
| Op temp (min) deg | -20 | Op temp (max) deg 100 |
| Conveying side material | GRIP TOP | |
| Conveying side colour | GREEN | |
| Underside Material | POLYESTER | |
| Underside feature | LOW FRICTION | |
| Underside colour | NATURAL | |
| Co- efficient of friction (u) | 0.1 | |
| Applications | Magnetic can elevators, flat and skid bed conveyors, box, parcel, carton conveying, incline/decline. | |
| Characteristics | Non-absorbant, oil/grease resistant, excellent tracking and edge wear tacky surface for extra grip and anti-static. | |
| Food approval | NO | |

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.