

F&D



15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059


PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: 3CFM GREEN



Thickness (mm)	4		
Weight (kg/m²)	4.5		
Max Width (mm)	3000		
Min Pulley diameter	120		
Nosebar Diameter (mm)	N/A		
Minimum back flex	180		
Load for 1% elongation (N/mm)	12		
Max working Tension	30		
Op temp (min) deg	-10	Op temp (max) deg	80
Conveying side material	PVC		
Conveying side colour	DARK GREEN		
Underside Material	POLYESTER		
Underside feature	UNCOATED		
Underside colour	WHITE		
Co- efficient of friction (u)	0.15		
Applications	General purpose conveyor belt, warehousing, food handling (fruits and vegetables), Wood Work, Packaging and Handling		
Characteristics	Anti-static.		
Food approval	NO		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.