



15 PELMET CRESCENT
 THOMASTOWN VIC 3074
 AUSTRALIA
 P.O. BOX 2106
 GREENVALE 3059

PHONE: (03) 9462 4544
 FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: DD24P



Thickness (mm)	2.7	
Weight (kg/m²)	3.2	
Max Width (mm)	1500	
Min Pulley diameter	120	
Nosebar Diameter (mm)		
Minimum back flex		
Load for 1% elongation (N/mm)		
Max working Tension	24	
Op temp (min) deg	-20	Op temp (max) deg 80
Conveying side material	DRY FABRIC	
Conveying side colour	WHITE	
Underside Material	DRY FABRIC	
Underside feature	LOW FRICTION	
Underside colour	WHITE	
Co- efficient of friction (u)	0.15	
Applications	Packaging, Mail, Transport, Paper Industry and other General applications	
Characteristics	Low friction belt on both sides. Suitable for diverter bar, wipe off and accumulation conveyor systems.	
Food approval	NO	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.