

F&D



15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059


PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: FNI-2E



Thickness (mm)	0.35		
Weight (kg/m²)	0.25		
Max Width (mm)	2400		
Min Pulley diameter	15		
Nosebar Diameter (mm)	2		
Minimum back flex	15		
Load for 1% elongation (N/mm)	2		
Max working Tension	3		
Op temp (min) deg	-30	Op temp (max) deg	80
Conveying side material	TPU		
Conveying side colour	CLEAR		
Underside Material	TPU		
Underside feature	IMPREGNATED FABRIC		
Underside colour	CLEAR		
Co- efficient of friction (u)	0.15		
Applications	Bakery/biscuit/cookie, bread chocolate/confectionary, food conveying and processing in general.		
Characteristics	Food suitable.		
Food approval	FDA/USDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.