

F&D



15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: LNF200



Thickness (mm)	4.3	
Weight (kg/m²)	4.6	
Max Width (mm)	500	
Min Pulley diameter	150	
Nosebar Diameter (mm)	N/A	
Minimum back flex	120	
Load for 1% elongation (N/mm)	18	
Max working Tension	-	
Op temp (min) deg	-30	Op temp (max) deg 80
Conveying side material	LEATHER	
Conveying side colour	GREY	
Underside Material	FABRIC	
Underside feature	POLYURETHANE SKIM	
Underside colour	BLUE	
Co- efficient of friction (u)	0.5	
Applications		
Characteristics	High co-efficient of friction, allows drive services to enable very high horse powers to be transmitted. Anti-static.	
Food approval	NO	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.