

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: LNL120



Thickness (mm)	4.1		
Weight (kg/m²)	4.9		
Max Width (mm)	500		
Min Pulley diameter	85		
Nosebar Diameter (mm)	N/A		
Minimum back flex	-		
Load for 1% elongation (N/mm)	12		
Max working Tension	-		
Op temp (min) deg	-30	Op temp (max) deg	80
Conveying side material	LEATHER		
Conveying side colour	GREY		
Underside Material	LEATHER		
Underside feature	LEATHER		
Underside colour	GREY		
Co- efficient of friction (u)	0.5		
Applications			
Characteristics	Much flexibility as the load carrying the core being centrally disposed allows the belt to flex readily around pulleys with small diameters. Large power of absorption. Anti-static.		
Food approval	NO		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.