



15 PELMET CRESCENT  
 THOMASTOWN VIC 3074  
 AUSTRALIA  
 P.O. BOX 2106  
 GREENVALE 3059

PHONE: (03) 9462 4544  
 FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

## DATA SHEET

### Belt Type: LNL200



<b>Thickness (mm)</b>	5.9	
<b>Weight (kg/m<sup>2</sup>)</b>	6.1	
<b>Max Width (mm)</b>	500	
<b>Min Pulley diameter</b>	150	
<b>Nosebar Diameter (mm)</b>	N/A	
<b>Minimum back flex</b>	-	
<b>Load for 1% elongation (N/mm)</b>	18	
<b>Max working Tension</b>	-	
<b>Op temp (min) deg</b>	-30	<b>Op temp (max) deg</b> 80
<b>Conveying side material</b>	LEATHER	
<b>Conveying side colour</b>	GREY	
<b>Underside Material</b>	LEATHER	
<b>Underside feature</b>	LEATHER	
<b>Underside colour</b>	GREY	
<b>Co- efficient of friction (u)</b>	0.5	
<b>Applications</b>		
<b>Characteristics</b>	Much flexibility as the load carrying the core being centrally disposed allows the belt to flex readily around pulleys with small diameters. Large power of absorption. Anti-static.	
<b>Food approval</b>	NO	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m<sup>2</sup> + or -5% variation, Teflon® content + or -2% variation.