

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: NT-90



Thickness (mm)	0.9		
Weight (kg/m²)	0.9		
Max Width (mm)	800		
Min Pulley diameter	5		
Nosebar Diameter (mm)	N/A		
Minimum back flex	5		
Load for 1% elongation (N/mm)	0.4		
Max working Tension	2		
Op temp (min) deg	-20	Op temp (max) deg	60
Conveying side material	POLYURETHANE		
Conveying side colour	WHITE		
Underside Material	POLYURETHANE		
Underside feature	LOW FRICTION		
Underside colour	WHITE		
Co- efficient of friction (u)	0.25		
Applications	Bread, Candy, spreaders, applications with no take up, weighing		
Characteristics	gloss		
Food approval	FDA/USDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.