

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: TAN RRT



Thickness (mm)	5.5		
Weight (kg/m²)	6		
Max Width (mm)	1500		
Min Pulley diameter	75		
Nosebar Diameter (mm)	-		
Minimum back flex	-		
Load for 1% elongation (N/mm)	6		
Max working Tension	12		
Op temp (min) deg	-10	Op temp (max) deg	70
Conveying side material	ROUGH TOP		
Conveying side colour	TAN		
Underside Material	NITRILE GRADE RUBBER		
Underside feature	NYLON/UNCOATED		
Underside colour	TAN		
Co- efficient of friction (u)	0.2		
Applications	Warehousing; incline conveyorbelt		
Characteristics	Oil resistant and abrasion resistant.		
Food approval	NO		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.