

F&D



15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059


PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: T04 AMBER



Thickness (mm)	0.65		
Weight (kg/m²)	0.7		
Max Width (mm)	2000		
Min Pulley diameter	4		
Nosebar Diameter (mm)	4		
Minimum back flex	15		
Load for 1% elongation (N/mm)	4		
Max working Tension	6		
Op temp (min) deg	-20	Op temp (max) deg	80
Conveying side material	THERMOPLASTIC P/U		
Conveying side colour	AMBER		
Underside Material	POLYESTER FABRIC		
Underside feature	IMPREGNATED FABRIC		
Underside colour	WHITE		
Co- efficient of friction (u)	0.15		
Applications	Flat and skid bed conveyors metal detectors, chocolate, enrobers and cooler conveyors.		
Characteristics	Easy to clean, non crack surface for enhanced hygiene, non abrobant oil grease resistant all purpose surface recommended for special embossing, excellent tracking and edge wear.		
Food approval	FDA/USDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.