

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: T073



| | | | |
|--------------------------------------|---|--------------------------|-----|
| Thickness (mm) | 0.7 | | |
| Weight (kg/m²) | 0.75 | | |
| Max Width (mm) | 1500 | | |
| Min Pulley diameter | 6 | | |
| Nosebar Diameter (mm) | 3 | | |
| Minimum back flex | 10 | | |
| Load for 1% elongation (N/mm) | 3 | | |
| Max working Tension | 6 | | |
| Op temp (min) deg | -30 | Op temp (max) deg | 100 |
| Conveying side material | SILICON | | |
| Conveying side colour | WHITE | | |
| Underside Material | POLYESTER FABRIC | | |
| Underside feature | IMPREGNATED FABRIC | | |
| Underside colour | WHITE | | |
| Co- efficient of friction (u) | 0.5 | | |
| Applications | Acceleration/imcline/decline belt, chocolate, confectionary, sweets. snacks, chewing gum, candy bars. | | |
| Characteristics | Adhesive/easy release, anti stickig, high grip surface. | | |
| Food approval | FDA/USDA | | |

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.