

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: T15/PX



Thickness (mm)	1.15		
Weight (kg/m²)	1.1		
Max Width (mm)	2000		
Min Pulley diameter	8		
Nosebar Diameter (mm)	4		
Minimum back flex	12		
Load for 1% elongation (N/mm)	4		
Max working Tension	10		
Op temp (min) deg	-30	Op temp (max) deg	80
Conveying side material	TPU		
Conveying side colour	WHITE		
Underside Material	POLYESTER/POLY URETHANE		
Underside feature	IMPREGNATED FABRIC		
Underside colour	WHITE		
Co- efficient of friction (u)	0.15		
Applications	Biscuit/cookie pre oven general conveyor rotary cutter belt + segments and applications.		
Characteristics	Abrasion fats, oil resistant, felxible in all directions.		
Food approval	FDA/USDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.