

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: T22/CC



Thickness (mm)	2.2	
Weight (kg/m²)	1.5	
Max Width (mm)	2000	
Min Pulley diameter	10	
Nosebar Diameter (mm)	5	
Minimum back flex	10	
Load for 1% elongation (N/mm)	2	
Max working Tension	20	
Op temp (min) deg	-30	Op temp (max) deg 100
Conveying side material	PET	
Conveying side colour	WHITE	
Underside Material	PET	
Underside feature	FABRIC	
Underside colour	WHITE	
Co- efficient of friction (u)	0.15	
Applications	Food conveyor belt, bakery, processing.	
Characteristics	Horizontal, high temperature resistant, microwave resisitant.	
Food approval	FDA/EU	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.