

# F&D

# O'CONNOR PTY LTD

15 PELMET CRESCENT  
THOMASTOWN VIC 3074  
AUSTRALIA  
P.O. BOX 2106  
GREENVALE 3059

PHONE: (03) 9462 4544  
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

## DATA SHEET

### Belt Type: TAR GRIP



<b>Thickness (mm)</b>	6	
<b>Weight (kg/m<sup>2</sup>)</b>	5.7	
<b>Max Width (mm)</b>	800	
<b>Min Pulley diameter</b>	80	
<b>Nosebar Diameter (mm)</b>		
<b>Minimum back flex</b>		
<b>Load for 1% elongation (N/mm)</b>		
<b>Max working Tension</b>		
<b>Op temp (min) deg</b>	-20	<b>Op temp (max) deg</b> 100
<b>Conveying side material</b>	FABRIC	
<b>Conveying side colour</b>	GREEN	
<b>Underside Material</b>	RUBBER	
<b>Underside feature</b>	IMPREG	
<b>Underside colour</b>	BLACK	
<b>Co- efficient of friction (u)</b>	0.5	
<b>Applications</b>	General Purpose; Warehousing; incline conveyor belt	
<b>Characteristics</b>	IMPREGNATED FEATURE	
<b>Food approval</b>	NO	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m<sup>2</sup> + or -5% variation, Teflon® content + or -2% variation.