

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: TT99



Thickness (mm)	1.5		
Weight (kg/m²)	1.3		
Max Width (mm)	2000		
Min Pulley diameter	10		
Nosebar Diameter (mm)	5		
Minimum back flex	20		
Load for 1% elongation (N/mm)	6		
Max working Tension	12		
Op temp (min) deg	-20	Op temp (max) deg	100
Conveying side material	COTTON UNCOATED		
Conveying side colour	BEIGE		
Underside Material	POLYESTER/URETHANE		
Underside feature	SKIM COAT		
Underside colour	WHITE		
Co- efficient of friction (u)	0.15		
Applications	Accepts shaped pieces of dough works well with a supertex moulder. For various bread products.		
Characteristics	Food industry, baking industry.		
Food approval	FDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.