

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544

FAX: (03) 9462 4744

A.C.N. 067 591 155

A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: UP90SW GREEN



Thickness (mm)	3		
Weight (kg/m²)	3.4		
Max Width (mm)	2000		
Min Pulley diameter	50		
Nosebar Diameter (mm)	N/A		
Minimum back flex	100		
Load for 1% elongation (N/mm)	14		
Max working Tension	16		
Op temp (min) deg	-20	Op temp (max) deg	100
Conveying side material	PU		
Conveying side colour	GREEN		
Underside Material	POLYURETHANE SKIM		
Underside feature	POLYURETHANE SKIM		
Underside colour	WHITE		
Co- efficient of friction (u)	0.15		
Applications	General Purpose		
Characteristics	Solid woven PU conveyor belt, oil resistant, easy to clean.		
Food approval	NO		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.