

F&D

O'CONNOR PTY LTD

15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: UU140 (MATT)



Thickness (mm)	1.5		
Weight (kg/m²)	1.7		
Max Width (mm)	2500		
Min Pulley diameter	25		
Nosebar Diameter (mm)			
Minimum back flex	40		
Load for 1% elongation (N/mm)	10		
Max working Tension	12		
Op temp (min) deg	-20	Op temp (max) deg	100
Conveying side material	TPU		
Conveying side colour	WHITE		
Underside Material	PET PUR		
Underside feature	IMPREGNATED FABRIC		
Underside colour	WHITE		
Co- efficient of friction (u)	0.15		
Applications	General conveyor belting. Bakery, confectionary packaging, general handling.		
Characteristics	Abrasion resistant, nose bar suitable, oils and fats resistant. Anti static and easy release.		
Food approval	FDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m² + or -5% variation, Teflon® content + or -2% variation.