

# F&D



15 PELMET CRESCENT  
THOMASTOWN VIC 3074  
AUSTRALIA  
P.O. BOX 2106  
GREENVALE 3059

PHONE: (03) 9462 4544  
FAX: (03) 9462 4744


A.C.N. 067 591 155 A.B.N. 24 067 591 155

EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

## DATA SHEET

### Belt Type: UU140 GLOSS



<b>Thickness (mm)</b>	1.5		
<b>Weight (kg/m<sup>2</sup>)</b>	1.65		
<b>Max Width (mm)</b>	2500		
<b>Min Pulley diameter</b>	25		
<b>Nosebar Diameter (mm)</b>			
<b>Minimum back flex</b>	40		
<b>Load for 1% elongation (N/mm)</b>	10		
<b>Max working Tension</b>	12		
<b>Op temp (min) deg</b>	-20	<b>Op temp (max) deg</b>	100
<b>Conveying side material</b>	TPU		
<b>Conveying side colour</b>	WHITE		
<b>Underside Material</b>	PET PUR		
<b>Underside feature</b>	IMPREGNATED FABRIC		
<b>Underside colour</b>	WHITE		
<b>Co- efficient of friction (u)</b>	0.15		
<b>Applications</b>	General conveyor belting. Food industry.		
<b>Characteristics</b>	Abrasion resistant, nose bar suitable, oils and fats resistant.		
<b>Food approval</b>	FDA		

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m<sup>2</sup> + or -5% variation, Teflon® content + or -2% variation.