

F&D



15 PELMET CRESCENT
THOMASTOWN VIC 3074
AUSTRALIA
P.O. BOX 2106
GREENVALE 3059

PHONE: (03) 9462 4544
FAX: (03) 9462 4744

A.C.N. 067 591 155 A.B.N. 24 067 591 155 EMAIL: belts@fdoconnor.com.au

SUPPLIERS OF CONVEYOR BELTING AND TRANSMISSION EQUIPMENT

DATA SHEET

Belt Type: WHITE HYGENIC NITRILE RUBBER



Thickness (mm)	1.5,3.0,4.5,6,10,12	
Weight (m2)	formula (specific gravity x thickness)	
Max Width (mm)	1200	
Min Pulley diameter	N/A	
Nosebar Diameter (mm)	N/A	
Minimum back flex	N/A	
Specific Gravity g/cm³	1.25	
Tensile Strength	6 Mpa (min)	
Op temp (min) deg	-25	Op temp (max) deg 90
Conveying side material	NBR	
Conveying side colour	WHITE	
Underside Material	NBR	
Underside feature	UNCOATED	
Underside colour	WHITE	
Co- efficient of friction (u)		
Applications	food handling	
Characteristics	oil resistant	
Food approval	YES	

Values shown are typical and are subject to change without notice. Before using, the user should determine the suitability of the product for its intended use and assumes all risk and liability in connection therewith. Specifications are subject to change without notice. Weight tolerance g/m2 + or -5% variation, Teflon® content + or -2% variation.